

SE 200 - Precise Water Level Measurement

The float-operated Shaft Encoder SE 200 was developed on the basis of the proven OTT Thalimedes for continuous measurement of water level.

A float-cable-counterweight system translates the water level change to the float pulley of the sensor. The rotation caused by this is converted into an electrical signal. A measured value is being calculated via the internal processing and is available via the interfaces SDI-12 and 4...20 mA.

The measuring principle features especially high accuracy and resolution. The well-known drift-free float principle with variable output signal is suitable for connection to **external data loggers** or **SPS systems**.

The SE 200 can be programmed via serial SDI-12 interface: measuring range, output range 4...20 mA, output format, float pulley circumference can be optimally adjusted to the measuring task.

Simple system integration

with standard signal 4 ... 20 mA

4 ... 20 mA

Output range can be allocated to a certain measuring range*

SDI-12

Adjustable* cm/mm or ft output

Optional flooding protection

Variable

Float cable or beaded cable

Absolute shaft encoder

Measuring range -30 m ... +30 m

Technical Data

Measuring range ±30 m

Available interfaces SDI-12 or 4 ... 20 mA

Resolution adjustable: SDI-12 0.01 or 0.001 m

4 ... 20 mA* 0.1 % of measuring range

Accuracy

SDI-12 ± 0.003 % of measuring range

4 ... 20 mA* ± 0.1 % of measuring range

Power supply $9 \dots 30 \text{ V}$ Temperature range $-20 \dots +70 \text{ °C}$ Relative humidity $10 \dots 95 \text{ %}$

Dimensions (L x W x H) 82 mm x 82 mm x 34 mm

Circumference float pulley* 200 mm **Veight** 250 g

Housing material fibre glass reinforced

plastics material

Protection type IP 54

OTT – Your partner for:

- Water level measurement in ground and surface water
- Discharge measurement
- Precipitation measurement
- Water quality measurement
- Data management and communication
- HydroService: consulting, training, installation and maintenance





OTT Messtechnik GmbH & Co. KG

Ludwigstrasse 16 87437 Kempten

Tel. +49 (0)831/5617-0

Fax +49 (0) 831/5617-209 info@ott-hydrometry.com

www.ott-hydrometry.com

^{*} programmable via SDI-12 commands